SYSTEMS | RENTAL | ONLINE



HDPE Mains Distribution

JB630Mh-1

Description

Lightweight and portable 630A mains connection unit for use on any temporary electrical installation. 5 No. 630A terminals, to support up to 240mm² cable connection, housed in a polyethylene enclosure. Enclosure incorporates a fitted carry handle and rails for ease of handling and stacking. External padlock hasp for security with an internal panel key lock protection shroud. Each terminal has respective M40 IP67 cable glands. Internal terminations are raised with phase individual phase clearance shrouds.

Enclosure

10mm thick 300-Grade High Density Polyethylene, offering good impact resistance, chemical resistance and high rigidity. Density of 0.96 g/cm³, less than 0.01% moisture absorption, impact strength of 10 kJ/m², service temperature from -50 to +80°C, with greater than $10^{14}\Omega$ surface resistance. IP54 Rated.




	Termination	Protection
Connection	5 No. 630A Terminals	N/A


Dimensions


H 258mm x W 605mm x D 486mm

Weight 12kgs











Scotland & North ide Rental Ltd, Unit 8 Shawfield Trade Park, Rutherglen, Glasgow. G731DB Tel: 01416470850
The Midlands ide Rental Ltd, Unit 4A & D, Zone 2, Burntwood Business Park, Ring Road, Burntwood, Staffs. WS73JQ Tel: 01543674759
The South ide Rental Ltd, Unit 13 Thurrock Trade Park, Oliver Road, Grays, Essex. RM203AL Tel: 01708863963

