

# Information Sheet for MD11 Spider

## MD11 Spider Product Description

A 32A three-phase (400V) rubber box distribution board designed to distribute temporary power from one area to another. The 32A plug and play distribution board is easy to relocate across site and blends in well with the surrounding environment.

All switchgear and Tri-rated wiring is housed within a solid cast rubber enclosure. An integrated transparent window is used to allow visual identification of the switchgear status and allow access in event of a trip.


## Key Benefits

Incoming 32A supply plug sits on a 6mm 5 core H07RN-F flying lead to allow ease of connection to a socket outlet. The enclosure incorporates a carry handle, stacking feet/raisers and all necessary electrical hazard warning identification.

The enclosure is a black, self-extinguishing, fully insulated, stackable, hard butyl rubber spider, with high resistance to chemical agents, atmospherics and current leakage. IK10 rated. IP55 rated. Plug on 1m Lead.



## Technical Information




### Specification

**32A 3PH Rubber Event Distribution**  
**In-**  
 32/3 Plug inlet  
**Out-**  
 3x 32/1 Panel sockets  
 Protected by 2pole 30mA RCBOs

### Notes

Switchgear-ABB  
 Sockets-Mennekes



### Product Socket Configuration

Inlet	Phase	Protection	Earth Leakage	IP Rating
125A	3	No	No	44
Outgoing	Phase	Protection	Quantity	IP Rating
32A	1	32A 2 Pole 30mA RCBO	1	44

### Other Features and Mechanical Information

Phase Indication	Power Indication	Lifting	Frame
		Handles	
Enclosure	Overall IP Rating	Size (mm)	Weight (kg)
	44	H300 x W400 x D350	10kg
Power Monitoring	Warranty		
	12 months		

Manufacturing Standard  
 IEC 61439: Part 2 etc  
 MD11spider\_Version1\_11/2021