

Information Sheet for MD42


MD42 Spider Product Description

32a Single-phase mains distribution unit for use on any temporary electrical installation. Equipment housed in a solid cast rubber spider enclosure, with integrated transparent MOD window protected switchgear, fixed carry handle and rising feet for ease of stacking.

Inlet on a rated flying H07RN-F lead to aid connection to generator or distribution board.



Technical Information




32A 1PH Event Distribution

In-
-32A 230V IP44 Plug - 1m Flying Lead

OUT-
4 x 16A 230V IP44 Panel Socket - 16A 2 Pole 30mA RCBO

Green LED Power Indication



Product Socket Configuration

Inlet	Phase	Protection	Earth Leakage	IP Rating
32A	3	230V Plug, 1m flying lead	n/a	44
Outgoing	Phase	Protection	Quantity	IP Rating
16A	3	4 x 16A 230V Panel Socket 2 pole 30mA RCBO	4	44

Other Features and Mechanical Information

Phase Indication	Power Indication	Lifting	Frame
Enclosure	Overall IP Rating	Size HxWxD(mm)	Weight (kg)
		H300 x W550 x D495	18
Power Monitoring	Warranty		
	12 months		

Manufacturing Standard
IEC 61439: Part 2 etc

MD42_Version1_01/2021