Temporary Power Distribution

TECHNICAL
DATA SHEET

GCP630A Lock off connections



Our Generator Connection Points are designed to restore power to critical applications. They can be fitted inside or outside of a building, allowing a safe and quick connection of a back-up generator to your facility's electrical system when required

TECHNICAL DATA

Incomer	Outgoing	Dimensions	Weight
3P + N + E Powerlock Drain.	Fully rated copper connections (hard-wired)	H750 x W500 x D250 (mm)	35kg

WARRANTY AND CERTIFICATION

All temporary power distribution equipment supplied is manufactured by IDE in the UK and is rigorously tested to BS 7671 standards, with 12-month certification provided as standard.

Our distribution systems are built using components that conform to the following international standards:
> EN 60309 – Plugs, socket-outlets, and couplers for industrial purposes
> EN 60529 – Degrees of protection provided by enclosures (IP code)
> EN 60947 – Low-voltage switchgear and controlgear

2 YEAR WARRANTY

All components and assemblies are covered by a 24-month manufacturer's warranty, ensuring reliability, safety, and regulatory compliance throughout the deployment period.

Temporary Power Distribution

TECHNICAL
DATA SHEET

GCP630 Lock off connections



PRODUCT FEATURES

- Indoor & Outdoor Use
- Powerlock type (Drain) connections for a quick easy connection
- Powder coated Stainless Steel enclosure
- Wall mounted fitted with M8 fixing points

POPULAR APPLICATIONS

The Generator Connection Box is designed to allow easy connection of a generator to restore power to critical applications such as hospitals, schools, airports, banks, and other commercial facilities. This removes the need for an electrician to make the connection.

T: 01543 574 111
E: enquiries@idesystems.co.uk
www.idesystems.co.uk