

Information Sheet for DS2 Temporary Installation Board

DS2 Temporary Installation Board Product Description

Designed to supply power to a range of mobile unit diagnostic modalities such as CT, MRI and PET scanners. Our MRI Connection Points are a vital component of most MRI installation projects. The DS2 are long lasting, robust with anti-corrosion. Enclosed In a crash frame to provide easy movement and stability on site.

Features and Benefits:

- > Indoor & outdoor use
- > Galvanised Crash Frame with fork lift pockets.
- > Incoming hardwire connection to M10 terminals with 250mm spreading distance.
- > Door interlocking handle with padlock facility.
- > 2 CAT 5e IP67 data sockets and a 2 wire IP54 Telephone connection point.
- > Optional 3 metre tails with Power lock connectors

Popular Applications

Temporary 125A or 250A three-phase mains distribution unit designed to supply Mobile MRI, CT and PET scanners with Marechal DS2 connection



Technical Information



Product Socket Configuration

Inlet	Phase	Protection	Earth Leakage	IP Rating
3P + N + E (Hardwire)	3	N/A	N/A	54
Outgoing	Phase	Protection	Earth Leakage	IP Rating
Option 1:				
250A Marechal DS2 Socket	3	250A 4 Pole MCCB	Yes	54
Option 2:				
125A CEEFORM Socket	3	125A 4 Pole MCCB	Yes	54

Other Features and Mechanical Information

Phase Indication	Power Indication	Lifting	Frame
On request	On request	Fork lift Pockets	Galvanised Steel
Enclosure	Overall IP Rating	Size (mm)	Weight (kg)
Powder Coated Stainless Steel (RAL 7035)	54	H1450xW890xD400	Approx. 80kg
Warranty	CAT 5e IP67 data sockets	2 wire IP54 Telephone connection	
12 months	2	Yes	

Manufacturing Standard
IEC 61439: Part 2 etc
ISO 9001-2015

DS2 Version1 05/03/2021